

Membrane Air Dryer/Single Unit Type

Series **IDG□A**



Standard dew point -20°C , -15°C , -40°C , -60°C

How to Order



IDG 30 □ A - □ 03 □ - □

Size ●

30
50
60
75
100

Standard dew point temperature and air flow rate ●

Symbol	Standard dew point (°C)	Flow rate by size					Outlet air flow rate (L/min [ANR])				
		30	50	60	75	100	Select from Series IDG				
Nil	-20	300	500								
H	-15	300	500								
L	-40	75	110	170	240	300					
S	-60	—	—	50	100	150					

● Option

Symbol	Contents
Nil	None (Standard)
P	With fitting for purge air discharge
R	Flow direction (Right → Left)

Note) In the case of two or more options, indicate them alphabetically.

● Thread type ●


Symbol	Type
Nil	Rc
N	NPT
F	G

● Accessory

Symbol	Type
Nil	None (Standard)
B	With bracket

Note) When symbol B is indicated, a bracket assembly with a part number shown in the table left below is included as an accessory.

JIS Symbol



Bracket Assembly (Accessory) Part No.

Part no.	Applicable model
BM64	IDG30□A, IDG50□A
BM65	IDG60□A, IDG75□A, IDG100□A

* With cap bolts (2 pcs.) and spring washers (2 pcs.)

● Port size

Symbol	Port size	Size				
		30	50	60	75	100
02	1/4	●	●	—	—	—
03	3/8	●	●	●	●	●
04	1/2	—	—	●	●	●