



For details about certified products conforming to international standards, visit us at www.smcworld.com.

Pneumatic Pressure Switch

Series IS3000

Model

Can be used for micro load, around 10 mA e.g. relays, programmable controllers, etc.

Easy electrical wiring

Wide space for wiring. Fixed wiring possible with G 1/2 connector.

Calibration range

0.1 to 0.7 MPa

Frequency: 1 cycle/sec

Service life: 10 million cycles

With indicator light



IS3100
(Gasket piping)

IS3000-02
(Rc 1/4 thread)



IS3110
(Gasket piping)

IS3010-02
(Rc 1/4 thread)

Specifications

Fluid	Air/Inert gas
Proof pressure	1.0 MPa
Max. operating pressure	0.8 MPa
Pressure adjustment range	0.1 to 0.7 MPa
Ambient and fluid temperature	-5 to 60°C (No freezing)
Contacts	1ab
Error of scale	±0.1 MPa
Hysteresis	0.05 MPa or less
Repeatability	±0.05 MPa
Enclosure	Equivalent to IP40
Mass	0.15 kg

Micro Switch Ratings


Model	IS3 ⁰ 00								IS3 ⁰ 10	
	Non inductive (A)				Inductive load (A)				Non inductive (A)	
	Load resistance		Light load		Inductive load		Motor load		Load resistance	
	N.C.	N.O.	N.C.	N.O.	N.C.	N.O.	N.C.	N.O.	N.C.	N.O.
Rated voltage (V)										
125 AC	5		1.5	0.7	3		2.5	1.3	0.1	
250 AC	3		1	0.5	2		1.5	0.8	—	
30 DC	4		2		3		3		0.1	
125 DC	0.4		0.05		0.4		0.05		—	

Insulation resistance: 100 MΩ or more at 500 VDC by megameter

Voltage resistance: 1500 VAC, 50/60Hz for 1 min. (When using switch with neon light: 1000 VAC for 1 min.)

How to Order

JIS Symbol



IS3 0 0 0 - 02 L1 -

Piping method

0	Rc 1/4 thread
1	Gasket piping

Micro switch load type

0	Standard
1	Micro load

Port size

Nil	With gasket
02	Rc 1/4
N02	NPT 1/4

Pressure display with scale plate

Nil	MPa
P	Both MPa and psi (Note)

Indicator light

Nil	None
L1	With neon light/110 VAC
L2	With neon light/220 VAC
L5	LED/24 VDC

Note) Micro load type: Not available "L2" option.