

Compact Pressure Switch

Series ZSE1/ISE1

How to Order

Rated pressure range/ Setting pressure range

Nil	0 to 1 MPa
L	0 to 100 kPa

Piping specifications

01	R 1/8 Note 1)
T1	NPTF 1/8 Note 1)

Note 1) M5 x 0.8 (female) threaded.

Positive pressure

ISE1

Vacuum

ZSE1

Piping specifications

00	For mounting on ZM ejector
01	Single mounting R 1/8 Note 2)
T1	Single mounting NPTF 1/8 Note 2)

Note 2) Single mounting style: M5 x 0.8 (female) threaded.

Wiring specifications

Nil	Grommet type (Lead wire: 0.6 m)
L	Grommet type (Lead wire: 3 m)
C	Connector type (Lead wire: 0.6 m)
CL	Connector type (Lead wire: 3 m)
CN	Without connector

Output specifications

14	NPN open collector 1 output w/o analog output, 3 turns adjustment
15	NPN open collector 1 output w/o analog output, 200 degrees adjustment
16	NPN open collector 2 output w/o analog output, 3 turns adjustment
17	NPN open collector 2 output w/o analog output, 200 degrees adjustment
18	NPN open collector 1 output w/ analog output, 3 turns adjustment
19	NPN open collector 1 output w/ analog output, 200 degrees adjustment
55	PNP open collector 1 output w/o analog output, 200 degrees adjustment

With Connector/How to Order

● Without lead wire (Connector 1 pc., Socket 4 pcs.) ... **ZS-20-A**

● With lead wire.....**ZS-20-5A-**

Note) When ordering switch with 5 m long lead wire, indicate both part numbers.

Ex.) ZSE1-01-15CN.....1 pc.
ZS-20-5A-50.....1 pc.

Lead wire length

Nil	0.6 m
30	3 m
50	5 m