

Sine Rodless Cylinder/Basic Type

Series REA

ø25, ø32, ø40, ø50, ø63



How to Order

Basic type

REA 25 - 300 -

Sine rodless cylinder
(Basic type)

Bore size

25	25 mm
32	32 mm
40	40 mm
50	50 mm
63	63 mm

Stroke (mm)

Refer to "Standard Stroke" below.


Port thread type

Symbol	Type	Bore size
Nil	Rc	25, 32, 40
TN	NPT	50, 63
TF	G	32, 50, 63

Made to Order
Refer to the table below
for details.

Specifications

Bore size (mm)	25	32	40	50	63
Fluid	Air				
Proof pressure	1.05 MPa				
Maximum operating pressure	0.7 MPa				
Minimum operating pressure	0.18 MPa				
Ambient and fluid temperature	-10 to 60°C (No freezing)				
Piston speed (Max.) ^{Note)}	50 to 300 mm/s				
Lubrication	Not required (Non-lube)				
Stroke length tolerance	0 to 250 st: $^{+1}_0$, 251 to 100 st: $^{+1.4}_0$, 1001 st or longer: $^{+1.8}_0$				
Holding force	363	588	922	1,470	2,260



JIS Symbol

Note) Piston speed above indicates the maximum speed. It takes approximately 0.5 seconds (for one side) after the body moves from the stroke end until it goes through the cushion stroke, while it takes approximately 1 second for both sides.

Standard Stroke

Bore size (mm)	Standard stroke (mm)	Maximum manufacturable stroke (mm)
25	200, 250, 300, 350, 400, 450, 500, 600, 700, 800	4000
32	200, 250, 300, 350, 400, 450, 500, 600, 700, 800	
40	200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000	5000
50	200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000	
63	200, 250, 300, 350, 400, 450, 500, 600, 700, 800, 900, 1000	6000

Note 1) Intermediate stroke is available by the 1 mm interval.

Note 2) Strokes over 2000 mm are available as made-to-order. (Refer to -XB11.)



Made to Order Specifications

(For details, refer to pages 1851 to 1954.)

Symbol	Specifications
-XB11	Long stroke type
-XC24	With magnet shielding plate
-XC57	With floating joint
-X206	Additional moving element mounting taps
-X210	Non-lubricated exterior specifications
-X324	Non-lubricated exterior specifications with dust seal
-X168	Helical insert thread specifications

Refer to "Pneumatic Clean Series" catalog for clean room specifications.

Mass

Bore size (mm)	25	32	40	50	63
Basic mass	0.71	1.34	2.15	3.4	5.7
Additional mass per each 50 mm of stroke	0.05	0.07	0.08	0.095	0.12

Calculation: (Example) REA32-500 • Basic mass1.34 (kg)
 • Additional mass0.07 (kg/50 st) 1.34 + 0.07 x 500 ÷ 50 = 2.04 kg
 • Cylinder stroke500 (st)

REA

REB

REC

Y

X

MQ

RHC

RZQ

D

X

Individual

X