

# Series VXZ



## How to Order (Single Unit)



VXZ2 **3** **0** **A** **A**

Fluid

**0** For Air

### Common Specifications

Seal material	NBR
Coil insulation type	Class B
Thread type	Rc*

\* One-touch fittings are attached to the resin body type.

### Size/Valve type

Symbol	Body size	Valve type
<b>3</b>	10A	N.C.
<b>A</b>		N.O.

### Body material/Port size/Orifice diameter







Symbol	Body material	Port size	Orifice diameter
<b>A</b>	Aluminum	1/4	10
<b>B</b>		3/8	
<b>C</b>	Resin	ø10 One-touch fitting	
<b>D</b>		ø3/8" One-touch fitting	
<b>E</b>		ø12 One-touch fitting	

Symbol	Body size	Valve type	Symbol	Body material	Port size	Orifice diameter
<b>4</b>	15A	N.C.	<b>F</b>	C37	1/2	15
<b>B</b>		N.O.	<b>G</b>	Stainless steel		

Symbol	Body size	Valve type	Symbol	Body material	Port size	Orifice diameter
<b>5</b>	20A	N.C.	<b>H</b>	C37	3/4	20
<b>C</b>		N.O.	<b>J</b>	Stainless steel		

Symbol	Body size	Valve type	Symbol	Body material	Port size	Orifice diameter
<b>6</b>	25A	N.C.	<b>K</b>	C37	1	25
<b>D</b>		N.O.	<b>L</b>	Stainless steel		

### Voltage/Electrical entry

Symbol	Voltage	Electrical entry
<b>A</b>	24 VDC	Grommet 
<b>B</b>	100 VAC	Grommet (With surge voltage suppressor) 
<b>C</b>	110 VAC	
<b>D</b>	200 VAC	
<b>E</b>	230 VAC	
<b>F</b>	24 VDC	DIN terminal (With surge voltage suppressor) 
<b>G</b>	24 VDC	
<b>H</b>	100 VAC	
<b>J</b>	110 VAC	
<b>K</b>	200 VAC	
<b>L</b>	230 VAC	Conduit terminal (With surge voltage suppressor) 
<b>M</b>	24 VDC	
<b>N</b>	100 VAC	
<b>P</b>	110 VAC	
<b>Q</b>	200 VAC	
<b>R</b>	230 VAC	
<b>S</b>	24 VDC	Conduit (With surge voltage suppressor) 
<b>T</b>	100 VAC	
<b>U</b>	110 VAC	
<b>V</b>	200 VAC	
<b>W</b>	230 VAC	
<b>Y</b>	24 VDC	Faston terminal 
<b>Z</b>	Other voltages	

For other special options, refer to pages 20 and 21.

Special voltage	24 VAC
	48 VAC
	220 VAC
	240 VAC
Special electrical entry direction	12 VDC
	DIN terminal with light
	Conduit terminal with light
	Without DIN connector
	Low concentration ozone resistant (Seal material: FKM)
	Oil-free
	G thread
	NPT thread
	With bracket
	Special electrical entry direction

Dimensions → Page 24 and after