

Related Products: Multi-holder

Series TMA

RoHS

- Can be used to secure the KE□ series exhaust valve with One-touch fitting.
- One-touch fitting New KQ2, union tee, elbow, and straight can also be secured.
- Depending on the number of holders required, they can be separated as desired. (Align the cutter with the cutting groove and cut the holder.)



Specifications

Ambient temperature	-20 to 60°C (No freezing)
Material	Flame resistant polypropylene (Equivalent to UL-94 standard V-0)
Color	Black

Model

Model	Stations	Applicable exhaust valve	Applicable One-touch fitting		
			Union tee	Union elbow	Straight union
TMA-04	10	—	KQ2T06-00A	KQ2L06-00A	KQ2H06-00A
TMA-06	8	KEA06	KQ2T08-00A	KQ2L08-00A	KQ2H08-00A
		KEB06			
TMA-08	8	KEA08	KQ2T10-00A	KQ2L10-00A	KQ2H10-00A
		KEB08			
		KEC-02			
TMA-10	6	KEA10	KQ2T12-00A	KQ2L12-00A	KQ2H12-00A
		KEB10			
TMA-12	6	KEA12	—	—	—
		KEB12			
		KEC-03			

Dimensions



Applicable tubing O.D. (mm)	Model	P	L	W	H ₁	H ₂	Q
4	TMA-04	16.1	160	26	10.2	15.5	17.5
6	TMA-06	19	151	28	11.4	17.9	18.6
8	TMA-08	21.7	172.5	31.8	12.6	20.3	18.6
10	TMA-10	25.4	151.2	35	15	24.3	22
12	TMA-12	28.1	167.3	37	16.2	26.7	22